

THINK CREATE PRINT



PMS 2031DW

34PPM.256MB RAM.1 GHZ DUAL CORE,DUPLEX.WIRELESS.



AVAILABLE ON



FOLLOW US



Contact US

Toll Free No.
18003099639
info@printmark.net.in
www.printmark.net.in

#startupindia

PRINTMARK MONO LASER PRINTER PMS 2031dw

Light, compact, and fast, the PMS2031DW PRINTER supports output up to 34 pages per minute, Connect via WIRELESS , USB or Ethernet available Extra High Yield toner offering up to 6,000 pages of output.

	Specification
Print Technology	Laser
Type of Machine	Single Function
Type of Printing	Mono
Cartridge Technology	Separate Drum And Toner
Minimum Speed Per Minute as per ISO/IEC 24734 in A4 Size	34 PPM
Time to First Page Out	7.9 Sec
Print Speed Duplex	18 IPM
Duplexing Feature Availability	Yes
Processor	1 GHz, Dual Core
Memory (RAM)	Standard: 256 MB / Maximum: 256 MB
Display	2-line All Points Addressable (APA) monochrome LCD display
Duty Cycle (No of Prints/month)	55000 pages
Supported Paper Size (Original/Image)	A4/A4 / Legal
Number of Main Paper Tray	1
Each Main Paper Tray Capacity	250
Bypass Tray Capacity	1
Output Tray Capacity	150 Sheets
Wireless	Yes
Standard Ports	802.11b/g/n wireless, (Type B), USB 2.0 Specification Hi-Speed Certified, Ethernet 10/100 Base tX (RJ-45)
Network Protocols	TCP/IP IPv6, TCP/IP IPv4, TCP, UDP
Resolution	2400 IQ (2400 x 600 dpi), 1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 600 x 600 dpi (default), 300 x 300 dpi
Media Size supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Aficio, A6
Media Type	Paper Labels, Card Stock, Plain Paper, Envelope
Yield of the cartridge supplied with Machine as per ISO/IEC: 19752/2004(E)	1200 pages
After market Cartridge Capacity	1200, 3000, 6000 pages
Imaging Unit Capacity	12000 pages
Print Languages	PCL5c Emulation, PCL5, PCL5e Emulation, PCLm, PCL6 Emulation, Direct Image
OS Support *	Windows 7 and above, SUSE Linux 12 and above, Ubuntu 16.04 and above, Red Hat Enterprise Linux WS 6.10 and above
Certifications	BIS, ROHS, CE, BEE, NABL Approved
Noise Level	Operating: 53 dBA (Print)
Size/Weight	H x W x D: x 216 x 355.6 mm x 332.74 mm/ 7.5 Kg
Warranty	1 Year Onsite Support

All information in this brochure is subject to change without notice. Printmark is not liable for any errors or omissions.

1- Average standard page yield value declared in accordance with ISO/IEC 19752. 2-" Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Printmark's product offerings based on the average number of pages customers plan to print on the device each month. Printmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals, paper loading intervals, speed, and typical customer usage. 3-" Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Printmark printers and MFPs. 4-Printers are sold subject to certain license/agreement conditions. 5-Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. 6-Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively.

*For Detailed OS Support Please visit our website www.printmark.net.in

© 2024 Printmark. All rights reserved. Printmark, the Printmark logo are trademarks of Printmark Technologies Pvt Ltd, registered in India.